MORE UNMATCHED THINFAX 1414LXM BENEFITS

PREVIEW FAXES ON SCREEN BEFORE SENDING.

VIEW RECEIVED FAXES.

CUSTOMIZE FAX COVER SHEETS.

PRINT OUT FAXES ON MOST PRINTERS.

CUSTOM TELEPHONE DIRECTORY FOR FREQUENTLY CALLED NUMBERS.

JUST PLUG IN AND GO! Since **MiniFax** software is built into the **ThinFax** card, there's no need to download communication or installation-driver software. Plus step-by-step manual makes it easy to use your **ThinFax** 1414LXM.

ENHANCED PORTABILITY. Data access arrangement technology built into cardeliminates need for heavy, bulky external DAA module. Simply attach lightweight 6-foot EXP phone cord to ThinFax card, and plug other end into wall jack.

LIFETIME WARRANTY. We even offer 48-hour repair/replacement.

100% **DATA TRANSMISSION ACCURACY**. Every time, guaranteed. **ThinFax 1414LXM** even automatically reduces speed to transfer data perfectly to slower receiving fax/modems.

WON'T INTERRUPT YOUR COMPUTER WORK. Insert and remove your **ThinFax** card without the hassle of rebooting your computer.

EXTENDS BATTERY LIFE. Automatic power-saving feature keeps your fax/modem performing perfectly longer.

LIFETIME TECHNICAL SUPPORT. Our technical experts are always available to help you get the most out of your ThinFax 1414LXM.

For more information, call (800) EXP-6922

SPECIFICATIONS

- ◆ Complies with PC Card (PCMCIA/JEIDA) standard
- ◆ Functions as Data/Fax modem and memory card simultaneously
- ◆ Low power consumption: @+5V, 150 mA max, 120 mA typical.
- ♦ Integrated Data Access Arrangement/One-piece cable with RJ-11 telephone jack.
- ◆ PC Card Type II Card Size 54.0mm x 85.6mm x 5 mm.
- ◆ Data mode protocols: CCITT V.32bis, V.32, V.23, V.22 A/B V.22bis and V.21 Bell 103 and 212A
- ◆ Error correction: V.42, MNP 2-4
- ◆ Data compression: V.42bis, MNP5
- ◆ Fax mode Protocols:

CCITTV.17, V.29, V.27ter, V.21 Ch. 2

- ◆ Automatic power save mode @+5V, 25mA
- ◆ Software compatibility: HP 100/200LX System Manager Compliant

Haves 1 "AT" Command Set

CC: Mail Datacomm

Fax Class 1 (EIA/TIA 578). Group III Compatible

- Auto retrain
- ◆ Tone, pulse and adaptive dialing
- Auto dial and auto answer
- Call Progress
- ◆ Compatible with Two wire dial-up telephone line.
- ◆ 2 or 4MB Low Power FLASH RAM (5V. only)
- ♦ V.54 Test & Diagnostics capability